



-1 Product properties :

The product is a 2k clear coat high gloss high solid made from high quality materials of acrylic resins, solvents and additives. This is to give high adhesion, hardness, and provide highly resistance to conditions and weather conditions. This is in addition to high resistance to



2 - Characteristics :

- Colorless
- Transparent
- High gloss
- Fast drying.
- Good adhesion and hardness.
- High resistance to conditions and weather conditions.
- High resistance to chemicals and solvents.

3 - Uses :

- Car repair and especially for applying over super mix basecoat.
- Steel Surfaces.

4 - Physical Properties:

- Color : Transparent
- Viscosity : 1.25 min. \pm 10 sec. Ford Cup No.4 at 25 °C
- Density : 1.00 \pm 0.02 gm/cm³
- Film Thickness : 50- 60 micron





5 - Instructions for use :

- **Mixing ratio:**
100 cm³ clear coat: 50 cm³ 2k hardener.
- **Dilution:**
Add (10 -15 %) 2K acrylic thinner

6 - Method of application :

It is suitable for application over both vertical and horizontal surfaces. It is applied in 2 coats by spraying. Allow flash off time between coats of 10-15 minutes.

7 - Drying time :

Drying time	at 25 °C	at 60 °C
Touch dry	4 hrs.	30 min.
Complete dry	16 hrs.	45 min.

8 - Shelf life :

2 years at 25 °C.

9 - Packaging :

1 Liter.

