



1 - Characteristic properties :

It is an alkyd clear coat that gives high gloss and high resistance against water and chemicals. It is suitable for clear coating over wood, windows, doors and boats. It can also be used for applying.

2 - Materials for application :

Synthetic Glossy Varnish and Thinner.

3 - Suitable substrates :

For wooden windows, wood works, boats, kitchens etc. It can be applied on both wood and walls, after proper priming. Surface must be dry, smooth and clean from dust, oils and greases. Priming may be required in some cases.

4 - Surface preparation :

Following degreasing flat with the coming sandpaper grades. P320 - P1000: to dry flat (mechanically or manually).

5 - Method of application :

Apply by spray gun or brush, thinned with El-Mohandes white spirit up to maximum 30 % to reach correct application viscosity.





6 - Physical properties :

Solid Content: 62 ± 2 % .
Coverage rate: 11 – 14 m²/Kg .
Density: 0.96 - 0.97 gm/cm³ .
Viscosity: 50 Sec. Cup Ford No.4 at 25°C .

7 - Drying time :

Dry to touch 2-3 hrs.
Hard dry 24 hrs.

8 - Gloss :

High gloss.

9 - Packaging :

1 kg and 3 kg.

10 - Shelf life :

24 months at 20 °C.

11 - Material safety data :

When using these products, it is required to comply with the national regulations for health and safety.

