



1 - DESCRIPTION :

A combination of selected solvents for Nitrocellulose Coatings to reduce the viscosity of the product before the application. Promotes good flow properties and suppresses blushing.

2 - PHYSICAL PROPERTIES :

Appearance: Liquid
Transparency: Clear



3 - CHEMICAL PROPERTIES :

Boiling point:	62 °C
Dry point:	168 °C
Density:	0.810 gm/cm ³
Water content:	Maximum %0.1

4 - APPLICATION::

It is suitable for nitrocellulose based sealer, primer, clear and pigmented topcoat.

5 - ADVANTAGE :

1. Fast drying
2. Strong dissolving power
3. Regular film evaporation
4. Blush resistant





5. Moderate evaporation rate
6. Excellent leveling and gloss
7. Not classified as a "hazardous air pollutant"
8. Highly miscible with other common organic solvents

6 - PACKING & STORAGE :

Available in 5.6 ltr.

To be stored in a dry and cool place, away from the sources of light and heat. Avoid sun exposure. Storage time of the product in the original package in the temperature 25°C is 24 months.

7 - HANDLING :

DISPOSAL : As per the guidance and legislations of the local authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

8 - SAFETY PRECAUTION

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove to fresh air, loosen collar and keep patient rested.
INGESTION	In case of accidental ingestion DO NOT INDUCES VOMITING. Obtain immediate medical attention.

